



TECHNICAL SPECIFICATIONS

Operation	Controlled or control-free entrance/exit in both directions	Safety Level Setting	With 2 security levels that can be defined as desired by the customer, turnstile is able to detect unauthorized passes and passes in the opposite direction and prevents or notifies, with audio or discreetly.
Chassis	AISI 304 quality stainless steel. Optional: Black stainless steel	Indicator	LED illumination around the upper cover and passage LEDs on the upper table. Optional: LED lightning on wings.
Wing	Angular winged, 10 mm tempered glass wing. Optional: Wood	Operating Voltage	110-230 VAC, 47-60 Hz
Functions	Works bidirectionally and allows the passage of a single person only with its microprocessor control, electronic passage memory feature saves in memory card swipes that occur before a passage is completed and allows them to pass without closing the wings. Optional: 2 x RS232 and 1 x RS485 communication ports.	Power Consumption	58 W during passage, 9 W during standby (for two wings)
Mechanism	With its adjustable mechanical torque control, the unit does not cause injury in the event of any jamming.	Operating Temperature	-10° / +70°
Sensors	6 reciprocal sensors in each corridors	Passage Speed	~40 persons/minute
Emergency Mode	Turnstile allows free entry by opening the wings when signal receipt from the fire detection system. During power failure the wings automatically switch to open position with adaptor. (fail safe)	Passage Width	50 cm
		Weight	~79 kg (Single Wing)
		Security Level	Deterrent
		Areas of Use	Suitable for indoor use
		Accessories	Logo Engraving, Sticker, Remote Control Unit, Stainless Steel Reader Apparatus, Meter, Button Control Unit, Stainless Steel Reader Leg, Stainless Steel Bottom Plate