



SPEED GATE TURNSTILES

LTOP201



TECHNICAL SPECIFICATIONS

Operation	Controlled or control-free entrance/exit in both directions	Safety Level Setting	With 4 security levels that can be defined as desired by the customer, turnstile is able to detect unauthorized passes and passes in the opposite direction and prevents or notifies, with audio or discreetly.
Chassis	AISI 304 quality stainless steel. Optional: Black, stainless steel	Indicator	LED illumination around the upper cover and passage LEDs on the upper table. Optional: LED lighting on wings.
Wing	Angular winged, 8 mm tempered glass Smoke Colored Glass.	Operating Voltage	110-230 VAC, 47-60 Hz
Upper Table	10 mm black tempered glass. Optional: Wood	Power Consumption	84 W during passage, 10 W during standby (for two wings)
Functions	Works bidirectionally and allows the passage of a single person only with its microprocessor control, electronic passage memory feature saves in memory card swipes that occur before a passage is completed and allows them to pass without closing the wings. Optional: 2 x RS232 and 1 x RS485 communication ports.	Operating Temperature	-10° / +70°
Mechanism	With its adjustable mechanical torque control, the unit does not cause injury in the event of any jamming.	Passage Speed	~40 persons/minute
Sensors	8 reciprocal sensors in every corridor	Passage Width	56 cm
Emergency Mode	Turnstile switches to emergency mode upon the receipt of a signal from fire detection system and wings open. In case of power shortage, wings automatically switch to open position with the power supplied from the accumulator (fail safe). -	Weight	~142 kg (Single Wing)
		Security Level	Deterrent
		Areas of Use	Suitable for indoor use
		Accessories	Logo Engraving, Sticker, Remote Control Unit, Stainless Steel Reader Apparatus, Meter, Button Control Unit, Stainless Steel Reader Leg, Stainless Steel Bottom Plate

