



TRIPOD TURNSTILES

LTT 303AS



TECHNICAL SPECIFICATIONS

Operation	Adjustable manual passage to either direction	Power Consumption	5 W during passages, 7 W during stand-by 
Frame	Angular lid, Slim case, two-legged, AISI 304 quality stainless steel, Optional: AISI 316 quality	Operating Temperature	-10° / +70° Optional: with heater -40°
Core Arms	CNC-machined, aluminum cast core and polished Ø40x2.5mm aluminum arms Optional: Stainless Steel Arms	Passage Speed	~25 persons/minute
Functions	Passage information (NC or NO), passage time, memory mode, audio warning, adjustable passage direction	Passage Width	45 – 50 cm
Mechanism	AISI 304 quality stainless steel.	Weight	~29,5 kg
Emergency Mode	Fail-Safe (arms drop during power failure) Optional: Fail lock	Security Level	Deterrent
Operating Voltage	The arms fall down with the signal received from fire detection system. Optional: Drop Arm	Indicators	Direction LEDS for both directions. Optional: Upper Lid
		Areas of Use	Suitable for indoor and outdoor use
		Accessories	Outdoor cover, Unauthorized Passage Notification System, Meter, Button Control Unit, Remote Control Unit, Stainless Steel Bottom Plate, Plexiglass Reader Assembly Kit, Reader Assembly Apparatus, RS232 Communication Unit.