


CodeNumber	Model	Terms of Payment & Delivery	ThruScan s9
869755498111	ThruScan s9	TT in Advance	
SPECIFICATIONS		2 Years Warranty, 10 Years Parts Supply Availability	
<ul style="list-style-type: none"> <li>International norms (NILECJ-0601 L1-5/IP40-41/IEC 348/EN60950 Class1) In conformity with CE European Union Norms and produced under ISO 9001: 2008 QMS</li> <li><b>Multi-Zone - 9 Real Detec on Zones(Up/Middle/Down and Left/Middle/Right)</b></li> <li><b>Whilst Normal Operation, displays IN/OUT Counters and Security Level on LCD without abbreviations so that Security Staff can easily understand</b></li> <li><b>Capable to Detect both Ferrous and Non-Ferrous Metallic Threat Objects Considered Dangerous by International Security Authorities. Can detect when tested both individually and in combination.</b></li> <li><b>Displays the Detected Metal Objects location on Both Side Panels LEFT/RIGHT from bottom to top with Continuous LED Zone Indicators</b></li> <li><b>Detects all threat objects even concealed, hidden with camouflage and/or wrapped. Impossible for such threat objects to pass through the WTMD without causing an alarm.</b></li> <li><b>No Interferences between Zones and No False Alarms</b></li> <li><b>Homogeneous Magnetic Field – No Dead Points – Same Detection Capability from bottom to top</b></li> <li>Detects Metals regardless their orientation</li> <li><b>10 sensi vity levels, 246 adjustable sensi vity steps at each</b></li> <li><b>Metal Density-Mass, Signal Strength Display at 10-level-VU meter</b> with green, yellow, red LEDs easily allows sight from distance</li> <li>Superior Discrimination, <b>Precise target location identification / Graphic zone display on Control Unit</b></li> <li><b>Auto Calibration (Automatically calibrates itself up to Environmental Conditions)</b> No Set Up Changes necessary when relocated and/or new Magnetic Objects brought Near-By</li> <li><b>Human Health friendly Very Low Frequency VLF technology, No affects to Pace Makers, Pregnant and Magnetic Media</b></li> <li><b>Green/Red bicolor traffic through LEDs</b> easily allows sight from distance 60 Persons/Minute and LED Alarm Indicators on side panels</li> <li>Operation Mode, Programming Parameters and Error Codes are Displayed on Wide 4x20 Characters LCD Screen</li> <li><b>Special Environmental Magnetic Interference Display Menu</b></li> <li><b>Adjustable audio alarm at 10 tons/level or Soundless (Mute) opera on</b></li> <li><b>IP 40-41 Protec on Level (EN 60529)</b></li> <li>Five Digit Incoming/ Outgoing &amp; Alarm Counters (Visible/Invisible) can be reset to Zero.</li> <li><b>Interference free Operation from other Electronic Devices and Does Not affect other Electronic Equipments. Necessary filtering precautions have been taken.</b></li> </ul>	<ul style="list-style-type: none"> <li>Four-digit changeable digital Pin Code</li> <li><b>Automatic Failure Display Function on LCD</b></li> <li><b>Reloading the factory default settings</b> by one-touch button</li> <li>Easy Programming and Display via <b>High Resolution LCD</b> (Liquid Crystal Display)</li> <li><b>4 Menu Languages</b>, Standard menu in English, German, Spanish and Turkish</li> <li><b>Relay output</b> for recording CCTV, Photo Taken-Recording, controlling turnstiles, etc. on Alarms</li> <li><b>STANDARD Built-in Uninterrupt ible Power Supply (UPS) enabling 2 hours operation without mains</b></li> <li>No seasonal adjustment requirement thanks to its Digital Electronic System (DSP)</li> <li>Easy-to-mount and assemble walk through metal detector (15 Minutes) Male/Female Socket-Connector Design</li> <li><b>Manufactured for 7/24 Con nuous Opera on</b></li> <li><b>74 cm Net Passage Width and 200 cm Net Passage Height</b></li> <li><b>Interference free Opera on at Middle Level Sensi vity of 10 cm Distance Constant Metals and 150 cm distance Moving Metallic Objects</b></li> <li>Audio-Visual alarms are no ceable at a range of 2 meters</li> <li><b>Micro-Processor Settings does not change when there is an electricity cut-off</b></li> <li><b>All Electronic Units (electronic unit, power supply, battery, adapter etc..) are inside the Equipment. No outer units.</b></li> <li><b>Floor Fixing Corrosion Resistant Metal Footers for proper assembly and durable use.</b></li> <li>Automatic Failure Display with Continuous Self-Checking of Key Parameters. <b>(BITE – Built-in Test Equipment)</b></li> <li>SCADA remote data communication and Networking of Multiple Metal Detectors - Send - Change settings by PC – <i>Software Optional</i></li> <li>Manufactured using the latest technology components and <b>Resistant to Vibration &amp; Impact</b></li> </ul> <ul style="list-style-type: none"> <li>➤ Weight: 53 kg</li> <li>➤ Gross weight: 59 kg</li> <li>➤ Opera ng voltage: 70VAC – 270VAC / 50Hz - 60Hz</li> <li>➤ Power: 10W Stand By- 20W (Alarm)</li> <li>➤ Package Dimensions (W x H x L):</li> </ul> <p>Box 1: 645 x255 x 2290mm Box 2: 240 x 250 x 805 mm</p> <ul style="list-style-type: none"> <li>➤ Ambient Temperature: -20°C to +70°</li> </ul>	 <p>ELEKTRAL A.S. Reserves the right to make changes without prior notice to the features, optionals, prices and "General Conditions of Sales, Delivery and Warranty". Please confirm details at order!..</p>	
<a href="http://www.elektal.com.tr">http://www.elektal.com.tr</a> <a href="http://www.thruscanmetaldetectors.com">http://www.thruscanmetaldetectors.com</a>		S9 is used by the Ministry of Justice Germany.	