CodeNumber	Model		Terms of Payment& Delivery	ThruScan sX
869755498112	ThruScan sX		TT in Advance	
SPECIFICATIONS			2 YearsWarranty, 10 YearsPartsSupplyAvailability	
 with CE European Union Multi-Zone - 9 Real Defi Separate Zone Sensitivit Whilst Normal Operativity without abbreviations s Capable to Detect both Considered Dangerous to both individually and in JAILHOUSE Sensitivity S SMART DETECTOR - Fasselects the correct sensi Displays the Detected II bottom to top with Confice Detects all threat object wrapped. Impossible for causing an alarm. No Interferences between Homogeneous Magnetic bottom to top Detects Metals regardles 20 sensi vity levels, 246 Program, Optional - 5 Pr Metal Density-Mass, Sig red LEDs easily allows sig Superior Discrimination, on Control Unit Auto Calibration (Autom Set Up Changes necessar Near-By Human Health friendly Makers, Pregnant and M Green/Red bicolor traffi Persons/Minute and LED Operation Mode, Program Adjustable audio alarm Adjustable audio alarm Adjustable Alarm Dura IR Protection Feature er Detection Mode Selection 	 International norms (NILECJ-0601 L1-5/IP44/IEC 348/EN60950 Class1) in conformity with CE European Union Norms and produced under ISO 9001: 2008 QMS Multi-Zone - 9 Real Detec on Zones(Up/Middle/Down and Le /Middle/Right) Separate Zone Sensitivity Setting Feature Whilst Normal Operation, displays IN/OUT Counters and Security Level on LCD without abbreviations so that Security Staff can easily understand Capable to Detect both Ferrous and Non-Ferrous Metallic Threat Objects Considered Dangerous by International Security Authorities. Can detect when tested both individually and in combination and Gives Audio-Visual Alarms. Can operate at JAILHOUSE Sensitivity Spectrums!. SMART DETECTOR – Fast and consistent calibration, Automatic Sensitivity Program selects the correct sensitivity for a specific weapon or a recognized test object Displays the Detected Metal Objects location on Both Side Panels LEFT/RIGHT from bottom to top with Continuous LED Zone Indicators Detects all threat objects even concealed, hidden with camouflage and/or wrapped. Impossible for such threat objects to pass through the WTMD without causing an alarm. No Interferences between Zones and No False Alarms Homogeneous Magnetic Field – No Dead Points – Same Detection Capability from bottom to top Detects Metals regardless their orientation 20 sensi vity levels, 246 adjustable sensitivity steps at each, Preset NILECJ Sensitivity Program, Optional - 5 Preset Programs Metal Density-Mass, Signal Strength Display at 10-level-VU meter with green, yellow, red LEDs easily allows sight from distance Superior Discrimination, Precise target location identification / Graphic zone display on Control Unit Auto Calibration (Automatically calibrates itself up to Environmental Conditions) No Set Up Changes necessary when relocated and/or new Magnetic Objects brought Near-By<		 Four-digit changeable digital Pin Code and Mechanical Lock Automatic Failure Display Function on LCD Reloading the factory default settings by one-touch button Easy Programming and Display via High Resolution LCD (Liquid Crystal Display) 4 Menu Languages, Standard menu in English, German, Spanish and Turkish Relay output for recording CCTV, Photo Taken-Recording, controlling turnstiles, etc. on Alarms STANDARD Built-in Uninterrup ble Power Supply (UPS) enabling 2 hours operation without mains Easy-to-mount and assemble walk through metal detector (15 Minutes) Male/Female Socket-Connector Design Manufactured for 7/24 Continuous Operation T4 cm Net Passage Width and 200 cm Net Passage Height Interference free Opera on at Middle Level Sensi vity of 10 cm Distance Constant Metals and 150 cm distance Moving Metallic Objects Installation and Operation without interference between two detectors up to a distance of min. 5 cm Audio-Visual alarms are no ceable at a range of 4 meters Micro-Processor Settings does not change when there is an electricity cutoff All Electronic Units (electronic unit, power supply, battery, adapter etc) are inside the Equipment. No outer units. Floor Fixing Corrosion Resistant Metal Footers for proper assembly and durable use. Automatic Failure Display with Continuous Self-Checking of Key Parameters. (BITE - Built-in Test Equipment) SCADA Remote Control Set - Send Receive- Change settings by PC, Audio-Visual alarms can be monitored Real Time by PC and can be logged into Hard Disk Software Optional REAL-TIME VIDEO PROSECUTION UNIT enabling recording Alarmed Visitors Pictures/All Visitors pictures or video with Time-Stamp to SD Card -30.000 Images Optional Weight: 56 kg Opera ng voltage:70VAC – 270VAC / 50Hz - 60Hz	Extract A.S. Reserves the right to make changes without prior notice below the features, optionals, prices and "General Conditions of Sales, belower and Warranty". Please confirm details at order!.
http://www.elektral.com.tr http://www.thruscanmetaldetectors.com			SX is usedby the Japan Embassies, Indian Police Department, Turkish Army.	